



TECHNICAL SPECIFICATIONS

Model Number	AC Input		Phase	Battery Voltage	AH Capacity 8 Hrs.	Max Output Current	Input* Cable (min)	Ground* Wire (min)	Battery Cables	Wt./ Lbs.	Dimensions
	Voltage	Amps									
LPTC3-4-18-208	208	5	3	12	250-625	100	3 x 12	12	1/0	66	29.5 x 16.2 x 12.5
	208	9	3	24	250-625	100	3 x 12	12	1/0	66	
	208	13	3	36	250-595	95	3 x 12	12	1/0	66	
LPTC3-4-18-240	240	4	3	12	250-625	100	3 x 12	12	1/0	66	29.5 x 16.2 x 12.5
	240	8	3	24	250-625	100	3 x 12	12	1/0	66	
	240	12	3	36	250-595	95	3 x 12	12	1/0	66	
LPTC3-4-18-480	480	2	3	12	250-625	100	3 x 12	12	1/0	66	29.5 x 16.2 x 12.5
	480	4	3	24	250-625	100	3 x 12	12	1/0	66	
	480	6	3	36	250-595	95	3 x 12	12	1/0	66	
LPTC3-4-24-208	208	8	3	24	250-530	85	3 x 12	12	1/0	66	29.5 x 16.2 x 12.5
	208	11	3	36	250-500	80	3 x 12	12	1/0	66	
	208	13	3	48	250-440	10	3 x 12	12	1/0	66	
LPTC3-4-24-240	240	7	3	24	250-530	85	3 x 12	12	1/0	66	29.5 x 16.2 x 12.5
	240	10	3	36	250-500	80	3 x 12	12	1/0	66	
	240	11	3	48	250-440	70	3 x 12	12	1/0	66	
LPTC3-4-24-480	480	3	3	24	250-530	85	3 x 12	12	1/0	66	29.5 x 16.2 x 12.5
	480	5	3	36	250-500	80	3 x 12	12	1/0	66	
	480	6	3	48	250-440	70	3 x 12	12	1/0	66	
LPTC3-6-18-208	208	5	3	12	250-720	115	3 x 10	10	1/0	66	29.5 x 16.2 x 12.5
	208	11	3	24	250-720	115	3 x 10	10	1/0	66	
	208	16	3	36	250-720	115	3 x 10	10	1/0	66	
LPTC3-6-18-240	240	6	3	12	250-875	140	3 x 10	10	1/0	66	29.5 x 16.2 x 12.5
	240	11	3	24	250-875	140	3 x 10	10	1/0	66	
	240	17	3	36	250-875	140	3 x 10	10	1/0	66	
LPTC3-6-18-480	480	3	3	12	250-875	140	3 x 12	12	1/0	66	29.5 x 16.2 x 12.5
	480	6	3	24	250-875	140	3 x 12	12	1/0	66	
	480	9	3	36	250-875	140	3 x 12	12	1/0	66	



P.O. Box 808 • 9404 Ooltewah Industrial Drive
 Ooltewah, TN 37363 USA
 Tel: 423 238 5700 • 800 238 VOLT (8658)
www.hawkerpowersource.com

Model Number	AC Input		Phase	Battery Voltage	AH Capacity 8 Hrs.	Max Output Current	Input* Cable (min)	Ground* Wire (min)	Battery Cables	Wt./ Lbs.	Dimensions
	Voltage	Amps									
LPTC3-6-24-208	208	9	3	24	250-625	100	3 x 10	10	1/0	66	29.5 x 16.2 x 12.5
	208	14	3	36	250-625	100	3 x 10	10	1/0	66	
	208	18	3	48	250-595	95	3 x 10	10	1/0	66	
LPTC3-6-24-240	240	9	3	24	250-690	110	3 x 10	10	1/0	66	29.5 x 16.2 x 12.5
	240	13	3	36	250-690	110	3 x 10	10	1/0	66	
	240	17	3	48	250-655	105	3 x 10	10	1/0	66	
LPTC3-6-24-480	480	4	3	24	250-690	110	3 x 12	12	1/0	66	29.5 x 16.2 x 12.5
	480	7	3	36	250-690	110	3 x 12	12	1/0	66	
	480	9	3	48	250-655	105	3 x 12	12	1/0	66	
LPTC3-10-24-208	208	16	3	24	250-1065	170	3 x 10	10	2/0	121	37.0 x 16.2 x 12.5
	208	24	3	36	250-1065	170	3 x 10	10	2/0	121	
	208	32	3	48	250-1065	170	3 x 10	10	2/0	121	
LPTC3-10-24-240	240	16	3	24	250-1250	200	3 x 8	10	2/0	121	37.0 x 16.2 x 12.5
	240	24	3	36	250-1250	200	3 x 8	10	2/0	121	
	240	29	3	48	250-1125	180	3 x 8	10	2/0	121	
LPTC3-10-24-480	480	10	3	24	250-1500	240	3 x 10	10	2/0	121	37.0 x 16.2 x 12.5
	480	15	3	36	250-1500	240	3 x 10	10	2/0	121	
	480	15	3	48	250-1125	180	3 x 10	10	2/0	121	
LPTC3-10-40-480	480	10	3	48	250-750	120	3 x 10	10	2/0	121	37.0 x 16.2 x 12.5
	480	14	3	72	250-720	115	3 x 10	10	2/0	121	
	480	15	3	80	250-690	110	3 x 10	10	2/0	121	
LPTC3-15-24-480	480	11	3	24	250-1625	260	3 x 12	12	2/0	121	37.0 x 16.2 x 12.5
	480	16	3	36	250-1625	260	3 x 12	12	2/0	121	
	480	20	3	48	250-1565	250	3 x 12	12	2/0	121	
LPTC3-15-40-480	480	14	3	48	250-1065	170	3 x 8	10	2/0	121	37.0 x 16.2 x 12.5
	480	21	3	72	250-1065	170	3 x 8	10	2/0	121	
	480	22	3	80	250-1000	160	3 x 8	10	2/0	121	

NOTES:

1. AC input voltage $\pm 10\%$
2. Frequency Hz 50/60
3. Battery Cable Length: 3 to 33 ft.
4. IP Protection IP20
5. Operating Temperature 32 to 104°F
6. Display - LCD

*Refer to current NEC or local codes.